

SOLLIS

ENVIROWEAVE

ROLLER | PANEL

SUNSCREEN
(ALUMINISED & NON ALUMINISED)

ENVIOWEAVE SUNSCREEN

Composition:	100% Polyester Trevira CS (PVC Free)
Width:	2,400mm
Weight:	155gsm approx
Thickness:	0.42mm approx
Light Fastness:	> 5 - 6, Depending on colour
Solar Properties:	Please refer to Solis Shading Coefficient table
Fire Retardancy:	Tested to AS1530.3, Permanently flame retardant, Product is designed and manufactured to comply with the Building Code of Australia requirements for class 2 to 9 buildings
Protection:	Mould and mildrew protection
Care Instructions:	Vacuum, Do not wash or dry clean Spongeable with damp cloth & mild detergent

ENVIOWEAVE SUNSCREEN – ALU

Composition:	100% Polyester Trevira CS (PVC Free)
Width:	2,400mm
Coating:	Aluminium
Weight:	155gsm approx
Thickness:	0.40mm approx
Light Fastness:	> 6 - 7, Depending on colour
Solar Properties:	Please refer to Solis Shading Coefficient table
Fire Retardancy:	Tested to AS1530.3, Permanently flame retardant, Product is designed and manufactured to comply with the Building Code of Australia requirements for class 2 to 9 buildings
Protection:	Mould and mildrew protection
Care Instructions:	Vacuum, Do not wash or dry clean Spongeable with damp cloth & mild detergent



flame retardant



ecospecifier
products.knowledge.solutions



SOLIS PRODUCTS

190 WILLOUGHBY ROAD
CROWS NEST NSW 2065

P +612 9439 9020

F +612 9439 9223

WWW.SOLISPRODUCTS.COM